



Product Service

EC-Attestation of Conformity

No. N8 05 02 49571 029

Holder of Certificate: Rockwell Samsung Automation447-6, Gongse-ri, Giheung-cup
449-902 Gyeonggi-do, Yongin-city
KOREA**Product:** Servo motor
(Servo Drive Motor)

This EC-Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 73/23/EEC relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: CPSA0104525**Date,** 2005-02-17

After preparation of the necessary technical documentation as well as the conformity declaration the required CE marking can be affixed on the product. Other relevant directives have to be observed.

Page 1 of 2



Product Service

EC-Attestation of Conformity

No. N8 05 02 49571 029

Model(s): CSD3-A5BX2, CSDL-A5BX1, CSD3-01BX2,
CSD3-02BX2, CSDL-02BX1, CSD3-04BX2,
CSDL-04BX1

Parameters:

Rated input voltage:	220-230 V a.c.
Rated input frequency:	50/60 Hz
Rated input current:	1.30 A(CSD3-A5BX2,CSDL-A5BX1) 2.00 A(CSD3-01BX2) 2.80 A(CSD3-02BX2,CSDL-02BX1) 6.48 A(CSD3-04BX2,CSDL-04BX1)
Rated output voltage:	0-230 V a.c.
Rated output frequency:	0-400 Hz
Rated output power:	Max.50 W(CSD3-A5BX2,CSDL-A5BX1) Max.100 W(CSD3-01BX2) Max.200 W(CSD3-02BX2,CSDL-02BX1) Max.400 W(CSD3-04BX2,CSDL-04BX1)
Number of phase:	3-Phase
Protection class:	I
Degree of protection:	IPX0
Overvoltage category:	III
Pollution degree:	2

Tested according to: EN 50178:1997



Product Service

EC-Attestation of Conformity

No. N8 05 02 49571 030

Holder of Certificate: Rockwell Samsung Automation447-6, Gongse-ri, Giheung-eup
449-902 Gyeonggi-do, Yongin-city
KOREA**Product: Servo motor
(Servo Drive Motor)**

This EC-Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 73/23/EEC relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: CPSA0104545**Date,** 2005-02-17

After preparation of the necessary technical documentation as well as the conformity declaration the required CE marking can be affixed on the product. Other relevant directives have to be observed.

Page 1 of 2



EC-Attestation of Conformity
No. N8 05 02 49571 030

Model(s): CSD3-10BX2, CSDL-10BX1

Parameters:

Rated input voltage:	220-230 V a.c.
Rated input frequency:	50/60 Hz
Rated input current:	7.0 A
Rated output voltage:	0-230 V a.c.
Rated output frequency:	0-400 Hz
Rated output power:	Max 1.0 KW
Number of phase:	3-Phase
Protection class:	I
Degree of protection:	IPX0
Overvoltage category:	III
Pollution degree:	2

Tested according to: EN 50178:1997



Product Service

EC-Attestation of Conformity

No. N8 05 02 49571 031

Holder of Certificate: Rockwell Samsung Automation447-6, Gongse-ri, Giheung-eup
449-902 Gyeonggi-do, Yongin-city
KOREA**Product:** Servo motor
(Servo Drive Motor)

This EC-Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 73/23/EEC relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: CPSA0104565**Date,** 2005-02-17

CE After preparation of the necessary technical documentation as well as the conformity declaration the required CE marking can be affixed on the product. Other relevant directives have to be observed.

Page 1 of 2



EC-Attestation of Conformity
No. N8 05 02 49571 031

Model(s): CSD3-15BX2, CSDL-15BX1

Parameters:

Rated input voltage:	220-230 V a.c.
Rated input frequency:	50/60 Hz
Rated input current:	9.5 A
Rated output voltage:	0-230 V a.c.
Rated output frequency:	0-400 Hz
Rated output power:	Max. 1.5 KW
Number of phase:	3-Phase
Protection class:	I
Degree of protection:	IPX0
Overvoltage category:	III
Pollution degree:	2

Tested according to: EN 50178:1997